

Table 2.2 Size limitations (continued)

	Tube (mm)	Min. width (mm)	Max. width (mm)	Max. height (mm)	Max. surf. (m ²)	Fabric std [*]	Fabric Black-out [*]	Ref. in graph
Series 70								
Cord/chain	25	350	1800	3400	6.1	✓		B1
				3200	5.7		✓	B2
	34	350	3000	2600	6.5	✓		B3
					6		✓	
Motor	34	350	3000	2600	6.5	✓		B5
					6		✓	
Crank control	34	350	3000	2600	6.5	✓		B7
					6		✓	
Series 130 and 170								
Cord/chain	20	350	1000	2200	2.2	✓		C1
				2000	2		✓	C2
	25	350	1600	1700	2.7	✓		C3
				1400	2.2		✓	C4
Series 170								
mini 2	25	400 (475)**	600	1700	1	✓		C5
				1400	0.8		✓	C6
Soft-raise	short	25	520 (600)**	775	1700	1.3	✓	C7
					1400	1		✓
long	25	700 (775)**	1600	1700	2.7	✓		C9
				1400	2.2		✓	C10
Series 300								
(See further in this paragraph)								n/a

* Thickness of standard fabrics is 0.25 mm.
Thickness of black-out fabrics is 0.4 mm.

** Dimensions between parentheses: when (with a softraise) an autostop is used, the minimal blind width is increased.

Table 2.3 Maximum total weights for control options

	Chain/cord	Softraise			Crank	Motor
		Mini 2	Short	Long		
ø20 mm	1 kg					
ø25 mm	2.5 kg	0.5 kg	0.9 kg	2.4 kg		
ø34 mm	3 kg				2.8 kg	3 kg
ø38 mm	5 kg					